

STARING SM 340



>> Remember Staring mixer is well known
for their good quality and long life

Staring SM 340

The special mixing mechanism of the SM 340 can be fitted with steel or rubber paddles as required. The mixing mechanism can be removed for cleaning and adjustment without the use of extra tools.

The mixer is transportable utilising two rubber wheels and a push/pull bar can be removed as necessary.

The electric motor has a thermal overload for protection.

The Mixer includes:

- Safety cover w/ bagsplitter
- Safety grid at discharge
- Magnetic safety cut-out

STARING

Staring Maskinfabrik A/S
Starengvej 9-11
DK-9700 Brønderslev

Tlf.: +45 9882 1622

Fax: +45 9882 5591

www.staring.dk

staring@staring.dk

CVR.nr. DK 2767 2701

>> The special s mixingshead om SM 340 can after request be mount with steel or rubberpaddel

Recommended for

Large aggregate concrete
Mortar
Refractory materials

Technical data

Gross volume app.	300 litre
Output app.	150-170 litre
Pan diameter	1000 mm
Main shaft, RPM	32
No. of mixer arms	3
Emptying height	830 mm
Total weight	425 kg
Total length	1260 mm
Total width	1200 mm
Total height	1050 mm

Motortype

Electric motor 3 x 400 V	5,5 kW	max 220 kg/charge
Electric motor 3 x 400 V	7,5 kW	max 300 kg/charge
Honda gasoline	6,6 kW	
Diesel motor		

